

Technical data sheet

KALIJEV SAPUN

Degreaser



product description:	Salt-containing soap formed from vegetable oils reacting with potassium hydroxide. Potassium soap is a soft, easily spreadable soap with colloid-granular structure, yellowish to dark and with odour specific for vegetable oils.
area of application:	It is used for washing walls in construction industry, diluted with water in 1:10 ratio, for degreasing greasy wood and metal surfaces, for lubricating assembly lines and PVC tubes and for various other manufacturing and industrial purposes.
thinning:	Dissolving in water in 1:10 ratio
consumption:	0,1-0,25 kg/m ² depending on the degree of soiling of the surface.
pH value:	9.5. - 10.5.
preparation and application material:	Before use, dissolve the material in clean warm water (in the ratio Kalijev sapun : water = 1:10) It is necessary to dissolve the material completely until foam is formed. The material is applied by brush or roller. After washing the surfaces, it is necessary to rinse and roughen them before applying dispersive paints for better adhesion of the coating on the substrate. Immediately after finishing the work, wash the tool with water. When carrying out the work, comply with construction regulations. In case of any questions, contact the sales and technical advisor of Chromos-Svjetlost.
safety measures:	General rules for construction work must be complied with. Keep out of reach of children. Wear protective equipment. Before use, read the Technical and Safety Sheet of the product.
transport and storage:	Store in dry and ventilated areas away from direct sunlight at temperatures ranging from +5 °C to +25 °C. Do not expose the product to direct sunlight, in winter protect from freezing.
shelf life:	Indefinite shelf life.
disposal of leftover product and packaging:	Empty the packaging of its contents completely. Dispose of it at a recycling yard. Legal persons must deliver the packaging as packaging waste to a licenced waste collector.
quality control:	Product quality characteristics are determined by internal production specifications as well as European and Croatian standards. The product is under constant supervision of the factory quality control of Chromos-Svjetlost d.o.o.
general remarks:	Before using the product, the customer must check the product, and upon noticing any incompatibility, the customer must stop the application of the product and contact the manufacturer, otherwise a complaint will not be accepted. The technical data are the result of our technical knowledge and experience, and are provided with the intention of achieving optimal results when working with Chromos-Svjetlost products. The data do not contain any legal or secondary obligation on the part of the manufacturer nor do they release the customer from the obligation to verify the suitability of the product for a specific purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible during individual deliveries. When applying the product on substrates that are not specified in corresponding documentation, consult the manufacturer. The manufacturer reserves the right to make further changes to the technical data sheet. Only the latest version is valid. Updated technical data sheets are available at www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail listed below. For more detailed information, please contact our technical service. Before use, read the safety labels on the product packaging, while the Technical and Safety Sheets are available on request.

July, 2021.

Quality and environmental protection management system certified by TUV Croatia;
Certificate numbers: 44 100 134668 / 44 104 134668

