

Technical Data Sheet

ULTRA DECKING CLEANER



product description:	ULTRA DECKING CLEANER is a highly effective concentrate for removing algae, moss and the first signs of mould.
intended use:	It is applicable on terraces, facades, canopies, fences and other outdoor surfaces (wood, stone, glass, concrete, ceramics ...).
assortment:	ULTRA DECKING CLEANER
thinner:	Water
density:	0.95 – 1.05 kg/l (EN ISO 2811-1)
volatile organic compounds content (VOC):	It is not subject to the VOC regulation
working conditions:	The temperature of the air, material and surface during processing must be higher than +10 °C, less than +25 °C, and relative humidity 75 %.
method of application:	The surface we want to clean is evenly coated with ULTRA DECKING CLEANER. Depending on the amount of mould, moss and algae, the product is applied diluted (max. 1:20 with water) or undiluted. Repeat if necessary. After brushing and washing, rinse the terrace with water. A high-pressure washer (mini-wash) can be used to make washing more successful. Wash the tool in soapy water after use. Completely dried wooden surfaces must be protected with ULTRA DECKING OIL. Terraces can be used 2 days after protection.
safety measures:	Prevent leakage and spillage into watercourses and drainage systems. Keep out of reach of children. Wear protective equipment. Read the safety data sheet of the product before use.
transport and storage:	Store in a dry and well-ventilated place out of direct sunlight at a temperature of +5 to +25 °C. Protect it from freezing in winter conditions.
shelf life:	In unopened packaging 3 years from the date of production.
product/packaging disposal:	Empty the packaging completely. Dispose of in accordance with valid regulations to an authorized waste collector.
quality control:	Product quality characteristics are determined by internal production specifications and European and Croatian standards. The product is under the constant supervision of factory quality control Chromos-Svjetlost d.o.o.
disclaimers:	Before using the product, please check its quality. In case of any major deviations from the declared properties of the product, stop the use and contact the manufacturer; otherwise any subsequent complaints will not be accepted. Technical data are the result of our technical and experimental knowledge, and are provided with the intention of achieving optimal results in working with CHROMOS- SVJETLOST products. The data does not contain a legal or secondary obligation of the manufacturer nor does it release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. Contact our Technical service before use on substrates not listed in the accompanying documentation. The manufacturer reserves the right to make any subsequent changes to the Technical Data Sheet. Only the latest edition is valid. Updated Technical Data Sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our Technical service for more detailed information. Be sure to read the safety labels on the product packaging before use. Safety Data Sheet is available on request.

October, 2021.

Quality and Environmental management systems certified in accordance with TÜV NORD Croatia;
Certificate No: 44 100 134668 / 44 104 134668

